

ASSEMBLY INSTRUCTION

SKU#517755/512871

NOTE: Please consult a qualified electrician if you are not certain of the installation or service.

CAUTION: Before starting the installation or service, disconnect power by turning off the circuit breaker or by removing the fuse at the fuse box. Apply caulk to mounting surface at top and sides.

1. Carefully unpack the fixture, lay out all parts on a clean surface.
2. Fasten the mounting strap onto outlet box with 2 outlet box screws.
3. Unscrew ring from screw collar loop and thread screw collar loop to the nipple A on mounting strap.
4. Using two pliers, twist open links at the two ends of the chain as shown. Hook one link to the loop and the other one link to the screw collar loop. Close the links. Place a piece of cloth between the plier jaws and the chain link to prevent scratching of the finish.
5. Weave fixture wires up through the loop, the chain, the ring, the canopy and the nipple A on mounting strap.
6. Take the ground wire from the house (supply), wrap it around the ground screw on the mounting strap so that the end of the ground wire is still loose, tighten the ground screw, and connect the ground wire from the fixture to the loose end of the ground wire from the house by twisting the ends together with pliers. Connect white wires from fixture to white wire (neutral wire) from supply circuit. Connect black wires from fixture to black wire (live wire) from supply circuit. Cover the connections by using the wire connectors provided.
7. Place tube onto the bushing (Fig.1). Put the cap and loop onto the nipple B (Fig.2). Spread out the fixture arms as shown in the Fixture Arm Spacing diagram (below). Fasten the curved arm to the cap with 2 screws provided (Fig. 2). Slide the top fixture arms to the bottom arms as shown in Fig. 3.
8. Unscrew the socket rings from the sockets. Place shades over sockets, refasten socket rings to secure them.
9. Install bulbs. (Sold separately).
10. Reconnect on the power.

